




ENGINEERING YOUR SUCCESS.

Pump & Motor Division Europe
Parker Hannifin Mfg. Germany GmbH & Co. KG
Neefestrasse 96
09116 Chemnitz, Germany
Ph: +49 (0)371 393 70
www.parker.com/PMDE

Pump & Motor Division Europe PVPlus



PV046R1E1AYNMFC



*Interactive 3D graphic, click to activate and rotate
(3D capable PDF viewer required)*

Technical Data	
Part No.	PV046R1E1AYNMFC
Series	Series PVplus – Design Series 47
Displacement	046 - 46 [cm ³ /rev] maximum, Frame Size 2
Rotation	R - Clockwise
Variation	1 - Standard
Mounting Interface / Shaft	E - SAE 4bolt-mount; SAE splined shaft
Ports / Threads	1 - BSPP ports; Metric Threads
Thru-drive pad and coupling	AY - SAE A mount, SAE A 9th coupling
Seals	N - NBR seals / FKM shaftseal
Controls Group	Hydromechanical Controls
Compensation Part 1	M - hydromechanical controls
Compensation Part 2	F - One spool Load Sensing control
Compensation Part 3	C - Standard with integrated pmax. Pilot
Weight [kg]	30

splined shaft 14T-12/24 DP, flat root, side fit ANSI B92.1



For performance data, dimensions and deviations from standards, see catalog.

Disclaimer:

Parker PMDE has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact their local Parker dealer for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's Standard conditions of sale.

PV046R1E1AYNMFC

