



VISA S.p.A. s.u.

GENERATING SETS and POWER SOLUTIONS

HEADQUARTERS & HEAD OFFICE
via I Maggio, 55 - Fontanelle (TV) 31043 - ITALY
tel: +39 0422 5091 - visa@visa.it - www.visa.it

MILAN area - LOCAL OFFICE
via Luigi Galvani, 12 - Zelo Buon Persico (LO) 26839 - ITALY
tel: +39 334 6387211

 VISA RENT - RENTAL DEPT. GENERATOR SETS ON HIRE tel: +39 0422 818633 rent@visa.it	 VALMEC - METALWORKS DEPT. METALWORKS tel: +39 0422 5093 info@valmec.it
 NETTUNO - WATER DEPT. IRRIGATION SOLUTIONS AND MOTORPUMPS tel: +39 0422 5092 info@nettuno-irrigazione.com	 METEOR - SOUNDPROOF DEPT. SOUNDPROOF MATERIALS and SOUND INSULATION SYSTEMS tel: +39 0422 509411 info@insonorizzanti.it

GENSET MODEL

Model: D 30 GX

Mechanical version: Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, modular fuel tank and collection basin without leak detection sensor (available as optional).

Fuel Tank Capacity l.: 120

Range: GALAXY

Baseframe model: GV20

Canopy model: GV20



GENERAL ENGINE DATA

Engine brand: DEUTZ

Engine model: F4M2011

Cylinders: 4

R.P.M.: 1500 r.p.m.

Cubic capacity: 3.11 l

Air intake: Aspirated

Standard voltage: 12 Vdc

Sae: -

BMEP: 800 kPa

Cooling: Oil

Flywheel P.R.P. Power: 28 kW

Flywheel E.P. Power: 29.4 kW

Electronic regulator: On request

Precision class: G2

Oil quantity: 13.00 l

Engine Antifreeze capacity: 0.00 l

Radiator type: Tropicalized

Heat from radiator: 16.00 kW

Heat from exhaust: 0.00 kW

Heat from radiation: 4.00 kW

Exhaust temperature: 600 °C

Cooling air flow: 30.00 m³/min

Combustion air flow: 2.03 m³/min

Exhaust gas flow: 6.28 m³/min

EU Stage: STAGE 2

RATED TECHNICAL DATA

Prime Power (PRP): 30.00 kVA

Prime Power (PRP): 24.00 kW

Emergency power (E.P.): 33.00 kVA

Emergency power (E.P.): 26.40 kW

Rated Power Factor (cosφ): 0.8

Windings: Three phases Series Star

Rated three-phase concatenated voltage: 400 V

Rated phase-neutral voltage: 230 V

Rated frequency: 50 Hz

Fuel type: Diesel

FUEL CONSUMPTION

Fuel Cons. at 100% (E.P.): 0.00 l/h

Fuel Cons. at 100% (P.R.P.): 8.00 l/h

Fuel Cons. at 75% (P.R.P.): 5.80 l/h

Fuel Cons. at 50% (P.R.P.): 4.00 l/h

GENERAL ALTERNATOR DATA

Alternator brand: STAMFORD

Alternator model: SOL2-P

P.R.P. Power: 30.0 kVA

E.P. Power: 33.0 kVA

Winding: Three phases Series Star

Terminals Number: 12.00 nr.

IP Protection: 23

Electronic regulator: AS540

Precision: 1.00 ± %

STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load:

The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power:

The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.

E.P. - Emergency power:

This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

VISA S.p.A. s.u. Headquarter - Head Office - Sede Legale - via I Maggio, 55 - 31043 Fontanelle (TV) ITALY - Cap.Soc. € 10.200.000,00 i.v.

SDI destination code: M5UXCR1 - R.E.A. TV-191097 - C.C.I.A.A. TV Iscr.Reg.Imp 02134890264 - VAT n°, Cod. Fisc. e P.Iva 02134890264 - PEC: visaspa.pec@legalmail.it

"Visa S.p.A. s.u." is a Single-shareholder Company subject to management and coordination by IPG S.p.A. - Milano, via Dante 14 - Company Register of Milan-Monza-Brianza-Lodi: n.12616930967